

WTC Economy Power Pallet Truck

SENSATIONALLY LOW PRICE!

*Please turn page for all
advantages + technical data*



WTC - BEST ERGONOMIC EQUIPMENT - AT LOWEST PRICES

WTC Power Pallet Truck LPT15

SENSATIONALLY LOW PRICE!

- The LPT-15 benefits from our design and engineering excellence.
- Good acceleration enhances efficient pallet entry and exit to increase productivity. No polar Electronic-control is programmable for specific tasks or operator skills.
- Smooth travel and lift combined with excellent control to reduce product damage and increase productivity.
- A heavy-duty 24-volt fused electrical system provides good travel and lift speeds.
- High quality hydraulic pump assure very low noise, maximum efficiency and durability.
- Drive unit is equipped with electromagnetic brake that is spring applied and electrically released. Brake is activated by the control handle position.
- Ergonomic control handle with buttons for raising, lowering and homing.
- Lift limit switch operates at maximum lift height to shut off pump motor.

TECHNICAL INFORMATION

Model	SL-LPT15	
Capacity	(kg/lb)	1500/3300
Lifting height	(mm/inch)	205/8,07
Min. height	(mm/inch)	85/3,3
Load center	(mm/inch)	600/23,6
Fork length	(mm/inch)	1150/45
Fork width	(mm/inch)	520/20,4
Max width	(mm/inch)	700/27,5
Wheels no	N°	4/2+1x or 2/2+1x
Swing angle		80
Steering angle		205
Walking speed	Km/h	Without load 5,2 With load 5,0
Lifting speed	Cm/sec	Without load 3,5 With load 2,7
Lowering speed	Cm/sec	Without load 2,7 With load 4,2
Motor	kW	0,8
Traveling motor	kW	0,7
Battery	V/Ah	24/60
Battery weight	(kg/lb)	32/70
Roller diam.	(mm/inch)	84x93(84x70)/3,3x3,6(3,3x2,7)
Steering roller	(mm/inch)	100x40/4x1,5
Driving wheel	(mm/inch)	240x90/9,4x3,5
Gradient (with load/without load)		5/6%
Brake		Electromagnetic
Speed controlling		Electronic-control
Transmission		Gears
Weight	(kg/lb)	270/595
Dimensions	X	310mm/12in
	S	47mm/1,8in
	x2	185mm/7,3in
	Y	1095mm/43in
	L	1590mm/62,5in
	B	160mm/6,3in
	Wa	1480mm/58in

Specifications are subject to change without notice