WTC QUICK-LIFT PALLET TRUCK

The WTC Quick-lift Pallet truck combines the best features of all pallet trucks. Quite possibly, the best pallet truck in the World!

Developed in Sweden.

STATE-OF-THE-ART TECHNOLOGY - LOW PRICES!



WTC PTQ Quick Lift Pallet Trucks

The WTC Quick lift Pallet Truck PTQ combines the best features of all pallet trucks. Quite possibly, the best pallet truck in the world. Designed in Sweden.

- Quick-lift pump. The forks reach the pallet on the first pump stroke and lift it on the second.
- Automatically switches over to normal lift when the load exceeds 150 kg/330 lbs.
- High capacity 2500 kg/5500 lbs.
- Perfectly ergonomic designed handle offers an excellent and comfortable grip in all situations and temperatures.
- 220° turning angle gives an outstanding maneuverability even in the tightest spaces, such as inside trailers.
- Low weight makes the pallet truck very handy to use.
- Quick and easy-change cassette valve houses the entire hydraulic control system and safety valve.
 - Made of stainless steel and can be replaced in a few minutes.

- Self-lubricating bearings, for preventing damage and assuring longer life.
- Hard chrome plate pistons and double seals ensure a tight and stable hydraulic system.
- Special valve makes lowering quickly without load, slower with heavy load.
- Overload relief valve safety prevents damage to equipment.
- Highest quality paint procedure galvanized + heat treated.
- 12 grease nipples for long durability and quiet operation.
- Re-enforced forks.
- 200 mm steering wheels for smooth and easy operation.
- Available with polyurethane, rubber or nylon wheels.
- Available with entry rollers for easy entry into pallets with bottom strings.

TECHNICAL DATA

TEOTIMOAE DATA	
Model	PTQ
Maximum capacity	5500lbs / 2,500 kg
Maximum height	8" / 200 mm
Lowered height	3,3"/85 mm
Fork lengths	As per customers request
Fork width outside	27" / 680 mm, 20 5" / 520 mm
Width of single fork	5.9" / 150 mm
Turning angle	220°
Total length	61"/1550 mm (with 45"/1150 mm fork length)
Total height	48"/1230 mm
Weight	155 lbs / 70 kg
Steer wheel dimension	7,8"/200 mm
Load wheel dimension	3,2x3,9"/82x99 mm (single load wheel) 3,2x2,7"/82x70 mm (bogie load wheel)

Specifications subject to change without notice.

