

WTC QUICK-LIFT PALLET TRUCK

The WTC Quick lift Pallet Truck combines the best features of all pallet trucks. Quite possibly, the best pallet truck in the world!



WTC - BEST ERGONOMIC EQUIPMENT - AT LOWEST PRICES!

WTC QUICK-LIFT PALLET TRUCK PTQ-2500

- Quick-lift pump. The forks reach the pallet on the first pump stroke and lift it on the second. Automatically switches over to normal lift when the load exceeds about 150 kg/330 lbs
- High capacity - 2500 kg/5500 lbs
- Perfectly ergonomic designed handle offers an excellent and comfortable grip in all situations and temperatures
- 220° turning angle gives an outstanding maneuverability even in the tightest spaces, such as inside trailers
- Low weight makes the pallet truck very handy to use
- Quick and easy-change cassette valve houses the entire hydraulic control system and safety valve. Made of stainless steel and can be replaced in a few minutes
- Self-lubricating bearings, for preventing damage and assuring longer life
- Hard chrome plate pistons and double seals ensure a tight and stable hydraulic system
- Special valve makes lowering quickly without load, slower with heavy load
- Overload relief valve - safety - prevents damage to equipment
- Highest quality paint procedure - galvanized + heat treated
- 12 grease nipples - for long durability and quiet operation
- Re-inforced forks
- 200 mm steering wheels - for smooth and easy operation
- Available with polyurethane, rubber or nylon wheels
- Available with entry rollers for easy entry into pallets with bottom stringers

TECHNICAL DATA

- Maximum capacity.....5500 lbs/2500 kg
- Maximum height.....8"/200 mm
- Lowered height.....3.3"/85 mm
- Fork lengths.....As per customers requests
- Fork widths outside.....27"/680 mm, 20.5"/520 mm
- Width of single fork.....5.9"/150 mm
- Turning angle.....220°
- Total length.....61"/1550 mm (with 45"/1150 mm fork length)
- Total height.....48"/1230 mm
- Weight.....About 155 lbs/70 kg
- Steer wheel dimension.....7.8"/200 mm
- Load wheel dimension.....3.2x3.9"/82x99 mm (single load wheel)
3.2x2.7"/82x70 mm (bogie load wheel)